

# FLOOR GRINDERS

SURFACE PREPARATION, FLOOR GRINDING & REMOVAL



2GC-NG  
2EC-NG

DUAL  
DISC

FLOOR  
GRINDER

STRIP  
GRIND  
REMOVE



MODEL #	2GC-NG	2EC-NG	2EC-NG
PART #	59300	59200	59600
POWER	Gasoline	Electric	Electric
ENGINE/ MOTOR	Honda GXV390	1.5HP, 20A, 115V	3HP, 15A, 230V
PHASE	N/A	Single	Single
AMPS	N/A	16	16
*RPMs	562	231	231
LENGTH	46"	46"	46"
WIDTH	27"	27"	27"
HEIGHT	39"	39"	39"
WEIGHT	282 lbs	260 lbs	260 lbs
MAX CORD LENGTH	NA	50 ft, 10 Gauge	100 ft, 10 Gauge

**PRODUCTION RATE:** 21.5" working width will grind approximately 400-500 Sq. ft. per hour at 1/32" depth with diamond tooling.

**INCLUDES:** 2 - Multi-Tooling Discs, which accepts MAGNA-TRAP® tools, 2-3" multi Vacuum Port and Water Port. Includes 80lbs of weight.

**REQUIRES:** 6 - Grinding Tools required per loading (3 Left & 3 Right handed tooling)

#### IDEAL FOR:

- Production grinding and floor cleaning in large and small areas: airports, parking decks, sports arenas, manufacturing plants
- Light cleaning or grinding of concrete surfaces
- Removing mastics, thin-set, epoxies and urethanes
- Leveling high spots or surface imperfections
- Lightly texturing slippery concrete surfaces

2GC-NG  
2EC-NG



**PRO TIP:** Add sand to surface to absorb moisture and prevent buildup on tooling.

**PRO TIP:** Be sure your tooling is level.

**PRO TIP:** Choose the proper extension cord length for all electric models, to avoid tripping breakers.

HANDLE EXTENSION

LEVELING LOCK

RECOIL STARTER GRIP (GAS ONLY)

ELECTRIC MOTOR

WATER HOOK UP

80LB WEIGHT

BEARING GREASE  
POINT ACCESSSES

ADJUSTABLE  
DUST SKIRT

ENGINE STOP SWITCH

ON/OFF SWITCH

THROTTLE (GAS ONLY)

ELECTRICAL PLUG

VACUUM PORT

WEIGHT TRAY

