



# CRETE-PLANE®

SURFACE PREPARATION, FLOOR GRINDING & REMOVAL

## CPM-10

### WALK BEHIND

### CRETE-PLANNER®

### LEVEL REMOVE



MODEL #	CPM-10G	CPM-10E
PART #	69100	69200
POWER	Gasoline	Electric
ENGINE/MOTOR	Honda GX390	7.5HP 230V/30A
PHASE	N/A	Three
AMPS	N/A	16.8
*RPMS	2446	2344
LENGTH	38"	38"
WIDTH	22.5"	22.5"
HEIGHT	41.5"	41.5"
WEIGHT	302 lbs	345 lbs
MAX CORD LENGTH	N/A	150 ft, 10 Gauge

#### PRODUCTION RATE:

10" working width planes approximately 500-700 sq ft per hour at 1/8" depth per pass.

#### PRODUCT NOTES:

6-Shaft and 8-Shaft easy change, side-loading drums available for this heavy-duty walk-behind unit.

#### IDEAL FOR:

- Aggressive removal
- Production scarifying
- Heavy coating removal


*Easy side loading drum!*



CPM-10

**PRO TIP:** On Asphalt applications, Use cooking oil on underside of machine to prevent build up of material.

**PRO TIP:** To achieve deeper depths EDCO recommends scarifying in steps, known as Step Scarifying. For example: To achieve 1/4" depth, make two 1/8" passes.



CPM-10 DRUM  
Part# 65270C  
(6 Shaft Drum)



CARBIDE CUTTERS  
8 Pt Part# 20326  
(6 Shaft Drum)



STEEL CUTTERS POINTED  
18 Pt Part# 20296  
(6 Shaft Drum)



CARBIDE MILLING CHUNKER  
7 Pt Part# 20336  
(8 Shaft Drum)

## CRETE-PLANE® START-UP PACKAGES & ACCESSORIES

PART #	ITEM	DESCRIPTION
A207	6 Shaft Start-up Package (Drum not included)	114 CP308T Carbides, 252 Spacers, 6 Shafts
A208	8 Shaft Start-up Package (Drum not included)	152 206T Cutters, 384 Spacers, 8 Shafts
65270C	CPM-10 6-Shaft Carbide Drum Loaded	One 10" 6-Shaft Drum w/Shafts, 119 Carbides & 238 Spacers

### LEVEL

Uneven Joints, Bumps, Uneven Surfaces

### REMOVE

Remove old Coatings and Paints, Swimming Pool Cool Deck, Removal of Contaminated Surfaces, Removal of Build ups (Oil, Grease, etc) Remove Rubberized Membranes

ENGAGE/DISENGAGE LEVER

COMES STANDARD  
6 SHAFT DRUM  
WITH 102 CUTTERS  
AND 252 SPACERS

KICK STAND

DEPTH CONTROL KNOB

VACUUM PORT

SIDE LOAD DRUM

