## CRETE-PLANE®

SURFACE PREPARATION, FLOOR GRINDING & REMOVAL



| CPM-8                               | MODEL#                | CPM-8G         | CPM-8E             | СРМ-8Р       |
|-------------------------------------|-----------------------|----------------|--------------------|--------------|
|                                     | PART#                 | 79300          | 79500              | 72600        |
| WALK<br>BEHIND<br>CRETE-<br>PLANER® | POWER                 | Gasoline       | Electric           | Propane      |
|                                     | ENGINE/<br>MOTOR      | Honda<br>GX270 | 5HP<br>230V/30A    | PPS<br>305cc |
|                                     | PHASE                 | N/A            | Single             | N/A          |
|                                     | AMPS                  | N/A            | 19.5               | N/A          |
|                                     | *RPMS                 | 2150           | 2160               | 2150         |
|                                     | LENGTH                | 37.5"          | 37.5"              | 37.5"        |
|                                     | WIDTH                 | 20"            | 20"                | 21"          |
| REMOVE                              | HEIGHT                | 38"            | 38"                | 43"          |
|                                     | WEIGHT                | 206 lbs        | 234 lbs            | 285 lbs      |
|                                     | MAX<br>CORD<br>LENGTH | N/A            | 100 ft<br>10 Gauge | N/A          |

**PRODUCTION RATE:** 8" Working Width planes approximately 350-500 sq ft per hour at 1/8" depth per pass. Removes traffic lines at 800-1000 lineal ft per hour

**PRODUCT NOTES:** CPM-8's optional Edger attachment allows the CPM-8 to get within 1 3/4" of any vertical surface. Gasoline, Electric or Propane power options available.

**INCLUDES:** Loaded general purpose carbide drum. 50 ft power cord (electric model only).


## IDEAL FOR:

- · Sidewalk trip hazard repair
- · Concrete coating removal
- · Floor preparation
- · Traffic line and marking removal
- · Creating non-slip surfaces
- Leveling Surfaces



PRO TIP: On Asphalt applications, Use cooking oil on underside of machine to prevent build up of material.

PRO TIP: To achieve deeper depths EDCO recommends scarifying in steps, known as Step Scarifying. For example: To achieve ¼" depth, make two 1/8" passes.



CPM-8 DRUM Part# 65050C (6 Shaft Drum)



CARBIDE CUTTERS 6 Pt Part# 20156



STEEL CUTTERS POINTE 18 Pt Part# 12206



CARBIDE MILLING CHUNKER 7 Pt Part# 20336

| CRETE-PLANE® START-UP PACKAGES & ACCESSORIES |  |   |  |  |
|--|--|---|--|--|
| PART#  | ITEM   | DESCRIPTION                                       |  |  |
| A201   | Start-up Package One (Drum not included)     | 78 CP206-T Cutters, 215 Spacers, 6 Shafts         |  |  |
| A202   | Start-up Package Two (Drum not included)     | 150 JRS501 Cutters, 175 Spacers, 6 Shafts         |  |  |
| A209   | Fine Setup Start-Up Pack (Drum not included) | 96 CP206-T Cutters, 174 Spacers, 6 Shafts         |  |  |
| 65050C                                       | CPM-8 General Purpose Carbide Drum loaded    | One 8" Drum w/6 Shafts, 78 Carbides & 215 Spacers |  |  |

## **LEVEL**

Uneven Joints, Bumps, Uneven Surfaces

## **REMOVE**

Remove old Coatings and Paints, Swimming Pool Cool Deck, Removal of Contaminated Surfaces, Removal of Build ups (Oil, Grease, etc) Remove Rubberized Membranes

