

FLOOR GRINDERS

SURFACE PREPARATION, FLOOR GRINDING & REMOVAL

SEC-NG	MODEL#	SEC-NG
	PART#	59800
SINGLE DISC	POWER	Electric
FLOOR	ENGINE/MOTOR	1.5HP, 115V/15A
GRINDER	PHASE	Single
	AMPS	13
	*RPMS	575
	LENGTH	43"
	WIDTH	21.75"
STRIP	HEIGHT	37.5"
GRIND REMOVE	WEIGHT	191 lbs
	ADDITIONAL MAX CORD LENGTH	25ft, 10 Gauge

PRODUCTION RATE: 10" working width grinds approximately 200-250 sq.ft. per hour at 1/32" depth per pass with diamond tooling.

INCLUDES: Multi-Tooling Disc, which accepts MAGNA-TRAP® tools, multi Vacuum Port and Water Port, 25 ft. 12 Gauge Power Cord attached with cord Hanger, 30lb weight pack

REQUIRES: 3 - Grinding Tools required per loading (directional Left-handed tooling)

IDEAL FOR:

- · Areas less than 1,500 square feet
- · Residential & commercial applications
- · Grinding Concrete
- · Repairing damaged concrete slabs
- · Removing urethanes or epoxy thin-coats
- Leveling high spots or surface imperfections
- Smoothing rough surfaces, rain marks or trowel marks
- Stripping mastics, thin-sets, paint build-ups, resins and more



PRO TIP: Add sand to surface to absorb moisture and prevent buildup on tooling.

