TG-10	MODEL#	TG-10G	TG-10E	TG-10P
	PART#	56600	56900	56700
TURBO GRINDER	POWER	Gasoline	Electric	Propane
	ENGINE/ MOTOR	Honda GXV390	5HP 230V,30A	Aztec 390cc 12V Starter
	PHASE	N/A	Single	N/A
	AMPS	N/A	19.5	N/A
STRIP GRIND REMOVE	*RPMS	1826	1500	1826
	LENGTH	43"	43"	43"
	WIDTH	21.25"	21.25"	21.25"
	HEIGHT	37"	37"	37"
	WEIGHT	195 lbs	245 lbs	254 lbs
	MAX CORD LENGTH	N/A	100 ft 10 Gauge	N/A

**PRODUCTION RATE:** 10" Working Width will grind approximately 400-500 Sq. ft. per hour at 1/16" depth with diamond tooling.

**INCLUDES:** 1 - 10" Multi-Tooling Disc & Standard 2" - 3" Multi Vacuum Port and water port, incudes leveling system. 50 ft power cord 50 ft power cord (electric model only).

**REQUIRES:** 3 Magna-Trap tools. (directional Left-handed tooling)

## STANDARD RIGID HEAD IS IDEAL FOR:

- Leveling uneven expansion joints, high spots, joint curls and bridge decks
- Remove coatings, build-ups, resins and more
- · Grind rough concrete surfaces.

## OPTIONAL FLEX HEAD IS IDEAL FOR:

- Preparing a smooth, flat floor to receive a new coating, removing coatings
- Grind rough concrete surfaces.