

FLOOR GRINDERS

SURFACE PREPARATION, FLOOR GRINDING & REMOVAL

2D-HDE	MODEL#	2D-HDE	2D-HDP
2D-HDP	PART#	58100	58200
DUAL HEAVY DUTY	POWER	Electric	Propane
	ENGINE/ MOTOR	5HP, 30A, 230V	LEHR LX600V
	PHASE	Single	N/A
FLOOR GRINDER	AMPS	23	N/A
GRINDER	*RPMS	385	703
STRIP GRIND	LENGTH	48"	48"
	WIDTH	26"	26"
REMOVE	HEIGHT	40"	44.5"
	WEIGHT	330 lbs	370 lbs
	MAX CORD LENGTH	100 ft, 10 Gauge	N/A

PRODUCTION RATE: 21.5" working width will grind approximately 800-1,000 Sq. ft. per hour at 1/32" depth with diamond tooling. Removable weights included.

INCLUDES: 2 - Multi-Tooling Discs, which accepts MAGNA-TRAP® tools, 2" - 3" multi Vacuum Port and Water Port. Includes 50' power cord (Electric only).

REQUIRES: 6 - Grinding Tools required per loading. (3 Left & 3 Right handed tooling)

IDEAL FOR:

- Heavy grinding of concrete surfaces in large areas. Removal of industrial strength coverings like waterproof membrane, polymer and thick epoxy
- Leveling high spots or rough concrete surfaces.



