

20" GASOLINE DOWNCUT CONCRETE AND ASPHALT SAW

MAX CUTTING DEPTH 7 3/4"



MODEL #	DS-20G	DS-20E
PART #	30100	30300
POWER	Gasoline	Electric
ENGINE/MOTOR	Honda GX390	7.5 HP, 230/460V
PHASE	N/A	Three
AMPS	N/A	12/6
*RPMS	3000	2880
BELTS	Cgd "V" Belt	Cgd "V" Belt
LENGTH	50"	50"
WIDTH	27"	27"
HEIGHT	38"	39"
WEIGHT	265 lbs	265 lbs

PRODUCT NOTES: 20" blade capacity. Positive locking throttle cable. Easy turn crank, for lowering and rising blades in and out of cut. Dual blade arbor cutting capabilities. Heavy-duty anti-vibration engine mount! Jack bolt belt tensioner prevents frame damage. 7-gauge steel blade guard with welded protective segment flap. Heavy-duty lifting bail for easy loading and unloading. Large screw-type depth control. Wide-T handles with rubber grips. Solid-steel lifting handles. High quality molded rubber wheels.

REQUIRES: 1 - 20" concrete or asphalt blade.

IDEAL FOR:

- Short run slab cutting
- Cured Contraction joints
- Patch repairs in asphalt and concrete
- Trenching



DS-20