

## SS-30

### 30" SELF PROPELLED CONCRETE AND ASPHALT SAWS

MAX  
CUTTING  
DEPTH  
12"



MODEL #	SS-30G	SS-30E
PART #	31400-30	34300-30
POWER	Gasoline	Electric
ENGINE/ MOTOR	Kohler CH980	15 HP, 460V/30A
PHASE	N/A	Three
AMPS	N/A	18.9
*RPMS	1900	1755
LENGTH	60.25	60.25
WIDTH	32"	32"
HEIGHT	51"	519"
WEIGHT	995 lbs	1094 lbs
MAX CORD LENGTH	N/A	250 ft, 10 Gauge

**PRODUCT NOTES:** Stress proof, precision machined, Steel arbor shaft. Includes electric start, 12 volt battery and heavy duty 30 amp charging system. Locking depth control allows operator to easily return to same depth, cut after cut. Positive-traction, chain-drive rear axle prevents slippage and improves cutting speeds. Swing away, rear 6.4 gallon fuel tank. Water pump included.

**REQUIRES:** 1 -3 0" Concrete or Asphalt Blade.

#### IDEAL FOR:

- Highway, road and bridge repair
- Utility installation
- Patch repairs in asphalt and concrete
- Trenching

**THIS SAW IS STANDARD WITH A 30" BLADE GUARD.**

*•RPM's are based on the saws blade speed for 30" blade capacity.*



SS-30