

TILESHARK FLOOR STRIPPER

SURFACE PREPARATION, FLOOR GRINDING & REMOVAL

TS-8	MODEL#	TS-8
	PART #	94400
MANUAL FLOOR STRIPPER	POWER	Electric
	ENGINE/ MOTOR	3/4 HP, 115V/15A
	PHASE	Single
	AMPS	10.8
	*RPMS	1850
	LENGTH	39.5"
	WIDTH	24.5"
REMOVE	HEIGHT	41"
	WEIGHT	149 lbs
	MAX CORD LENGTH	50 ft 10 Gauge

PRODUCTION RATE: Remove up to 200 sq ft per hour of vinyl or other related soft material (Sq footage amounts and time schedules will vary based on material and adhesion)

PRODUCT NOTES: Provides 1850 oscillating hits per minute, Push plate and built-in weight assists in removing material. 25 ft. 12 gauge power cord attached.

IDEAL FOR:

- · Removing vinyl tile
- · Linoleum tile
- VCT
- · Industrial build-ups
- Carpeting



*Width based on handlebars.

PRO TIP: On concrete, position the scraper blade bevel side up for removing soft floor covering.



8" RIGID SCRAPER BLADE Part# 28040 (Pack of 5)



8" FLEX SCRAPER BLADE Part# 28030 (Pack of 5)



12" FOAM RUBBER BACKING SCRAPER BLADE Part# 28060



8" LINOLEUM & CARPET SLICER BLADE Part# 28050

HANDLE

HANDLE

HANDLE

ON/OFF SWITCH

AC POWER CORD

ANGLE ADJUSTMENT MECHANISM

Note: Raise handle slightly to release downward pressure on angle adjustment mechanism before aftempting blade angle adjustment.

LIFTING BAIL

OSCILLATING ACTION BLADE HOLDER

EASY ACCESS GREASE POINT